

BS-634 Wall Mount Speaker

Features:

- Innovative Speaker Design
- Low Profile
- Easy and Quick Installation
- Ideally Suited for BGM and Announcements



Wall Mount Speaker

The **BS-634** is a wall-mounted speaker matched with a supplied plug-in speaker receptacle, for easy installation.

The 6W rated input BS-634 is a 5" (12cm) cone-type speaker. An M4 screw terminal input connector allows easy connections. The speaker is driven on a high-impedance (100V or 70V) line, with rated inputs.

The **BS-634** enclosure's design proportions are based on the Golden Ratio (1: 1.618). A low profile blends in well with room décor.

Both vertical and horizontal installations are possible. Enclosure and grille net colour is off-white.

Rated Input	6W
Impedance	100V line: 1.7 k Ω (6W), 3.3 k Ω (3W) 70V line: 1.7 k Ω (3W), 3.3k Ω (1.5W)
Sensitivity (1m/1W)	90dB
Frequency Response	120 – 18,000 Hz
Speaker Component	5" (12cm) cone-type
Input Connector	M4 screw terminal, distance between barriers: 11mm (0.43")
Finish	Enclosure: HIPS resin (fire resistant grade UL94 V-0 or its equivalent), off-white (RAL 9010 or equivalent colour) Net: Surface-treated steel plate, off-white (RAL 9010 or equivalent colour), paint
Dimensions	219 (W) × 330 (H) × 80 (D)mm (8.27" × 12.99" × 3.15")
Weight	1.3 kg (2,87 lb)